

Outlet Express

Logistics and
warehousing

E-commerce

Catering
clothing

Financial
insurance

HGRT

Hello, future

This is by far the smoothest Label printer.

No cumbersome Only wonderful

- ★ Automatic induction, positioning test
- ★ Professional wear-resistant print head, designed for printing
- ★ Stable performance, high-speed and clear printing
- ★ It can print continuously for every day with a printing length of 30KM.
- ★ Ribbon-free, ribbon-free, ink-free
- ★ Worry-free printing, mobile phones and small programs can print easily.



HG 42

Thermal Label **Printer**


Outlet Express

Logistics and
warehousing

E-commerce

Catering
clothingFinancial
insurance

HGRT



HG 42

Thermal Label Printer

Printing Features

Resolution	203 DPI
Print method	Direct Thermal
Max.print speed	152 mm(6")/s Max.
Max.print width	108 mm (4.25")
Max.print length	1778 mm (70")

Media

Media type	Continuous, gap, black mark, fan-fold and punched hole
Media width	32~118mm (1.0"-4.6")
Media thickness	0.06 ~ 0.25 mm (2.36 ~ 9.8 mil)
Media core diameter	25.4 ~ 76.2 mm (1 " ~ 3 ")
Label length	10 ~ 1778 mm (0.39 " ~ 70 ")
Label roll capacity	127 mm (5") (External diameter)

Performance Features

Processor	32-bit CPU
Memory	8MB Flash Memory/ 8MB SDRAM
Interface	Standard:USB Options: Serial /LAN/WIFI/Bluetooth

Fonts/Graphics/Symbologies

Internal fonts	8 alpha-numeric bitmap fonts, Windows fonts are downloadable from software.
1D barcode	Code 39, Code 93, Code 128UCC, Code 128 , subsets A, B, C, Codabar, Interleaved 2 of 5, EAN-8,EAN-13, EAN-128, UPC-A, UPC-E, EAN and UPC 2(5) digits add-on, MSI, PLESSEY, POSTNET, China POST
2D barcode	PDF-417, Maxicode, DataMatrix, QR code
Rotation	0°, 90°, 180°, 270°
Emulation	TSPL, EPL

Physical Features

Dimension	226.5(D)×180(W)×162.5(H)mm
Weight	1.33kg

Reliability

Warranty	12 months
Print head life	30 km

Software

Driver	Windows/Linux/Mac
SDK	Windows/Android/iOS

Power adaptor

Input : AC 100-240V, 50 ~60Hz Output : DC 24V, 2.5A, 60W

Options

Factory Options	①USB ②usb+Lan+serial ③usb+bluetooth ④usb+WIFI
-----------------	---

Environmental Conditions

Operation environment	5 ~ 40°C (41~104°F) , Humidity: 25 ~ 85% non-condensing
Storage environment	-40 ~ 60°C (-40~140°F) , Humidity:10 ~ 90% non-condensing