

RETSOL RTP-82UW

Thermal Receipt Printer

- » New sleek shell design
- » 200mm/s Printing Speed
- » Wall mount capable
- » Easy drop-in paper loading
- » Intelligent cutter control system
- » Order comes remind
- » USB + WiFi Interfaces



RTP-82UW

Technical Specifications

Printing method	Direct thermal
Paper width	58±0.5mm / 79.5±0.5mm
Print width	72mm/ 76mm/ 80mm/ 64mm/ 48mm/ 52mm
Column capacity	576 dots/line (adjustable by command)
Printing speed	200mm/s
Interface	USB + WiFi
Line spacing	3.75mm (Adjustable by commands)
Column number	80mm paper: Font A - 42 columns or 48 columns/Font B - 56 columns or 64 columns/ Chinese, traditional Chinese - 21 columns or 24 columns
Character size	ANK, Font A:1.5×3.0mm (12×24 dots) Font B:1.1×2.1mm (9×17 dots) Chinese, traditional Chinese:3.0×3.0mm(24×24 dots)
Auto cutter	Partial
Input buffer	128 Kbytes
NV Flash	256 Kbytes
Power adaptor	Input: AC 100-240V/50~60Hz; Output: DC 24V/205A
Printer Input	DC 24V / 2.5A
Cash drawer	DC 24V / 1A
Weight	0.97 Kg
Dimensions	180 x 140 x 134.1mm (D x W x H)
Operation environment	Temperature (0~45°C) humidity (10~80%)
Storage environment	Temperature (-10~60°C) humidity (10~90%)
Cutter life	1.5 Million cuts
Printer head life	150 Km
Emulation	ESC/POS
Driver	Windows/JPOS/OPOS/Linux/Android/Mac
Utility	Windows & Linux test Utility
SDK	IOS/Andoid/Windows
Warranty	One year factory warranty*

Applications



Supermarket



Catering



Ticketing



Medical Care



* Warranty - Against Manufacturing Defects on the Printer
Specifications are subject to change without notice.

