

POINT-OF-SALE PRINTER

TP900

NGX

3" inch
Paper Width
with auto
cutter

easy to
set up
and use



Compatible
with ESC/POS
commands

Best print
speed with
260 mmps

USB, LAN,
and Serial
port

Windows /
Linux / An-
droid support

APPLICATIONS

Authorized Dealer



Apparel



Footwear



Groceries



Restaurants



Bakeries



Many more

SPECIFICATION

TP900



Printing method	Direct thermal
Printing speed	260mm/s
Paper width	79.5 +- 0.5mm
Printable area	72mm(adjustable by commands)
Maximum paper diameter	dia 80 mm
Paper thickness	0.06 - 0.08mm
Column capacity	576 dots/line 512 dots/line
Line space	3.75mm(Changeable by commands)
Commands	Compatible with ESC/POS
Interface type	USB+Serial+Lan
Character size	ANK, FontA: 12x24 dots Font B: 9x17 dots
Operating System	Windows / Linux / Android Supported
Bar code	UPC-A/UPC-E/JA(EAN13)/JAN8(EAN8)/CODE39/ITF/ CODABAR/CODE93/CODE128
Code page	PC347(Standard Europe), Katakana, PC850(Multilingual), PC860(Portuguese), PC863(Canadian-French), PC865(Nordic), WestEuropeGreek, Hebrew, East Europe, Iran, WPC1252, PC866(Cyrillic#2), PC852(Latin2), Pc858, Iranii, Latvian, Arabic, PT151(1251)
Cutter	Partial
Cutter life	1.5 million cuts
Print head life	100KM
Input buffer	64 Kbytes
NV Flash	256 Kbytes
Power adaptor	AC110V/220V, 50-60Hz
Power source	DC 24V/2.5A
Input voltage	DC 24V/2.5A
Cash drawer output	DC 24V/1A
Work environment	Temperature: 0-45C , humidity: 10-80RH%
Storage environment	Temperature: -10-60c , humidity: 10-90RH%
Dimension	183.3x140x141.5mm (DxWxH)
Gross weight	1.0 KG



LAN
Port



Serial
Port



USB
Port

Compact
Design

Easy
Installation

Auto
Cutter

Cost
Effective

Best-in-class
Speed

NGX Technologies Pvt. Ltd.

#12,20th Cross, Malagala, Nagarahabavi
2nd stage, near VijayaNetralaya, Bengaluru,
Karnataka 560091

www.ngxtechnologies.com

Printer Accessories

Adapter
Driver CD

Power Cord
Instruction
Manual

LAN Cable
Paper Roll

USB Cable
Serial
Cable